

DANTHANE® I 25KB-POWDER

DESCRIPTION

DANTHANE® 125KB-Powder is a polyester based, aromatic TPU, already coloured in blue. This TPU powder is best suitable for coatings and films, that must show high flexibility also at low temperatures. DANTHANE® 125KB-Powder is mainly used at the production of blue coloured transport elements (transport and conveyor belt coatings) as well as for flat belts and flexible materials for containers.

PRODUCT CHARACTERISTIC

	Values	Method
Aspect	Blue coloured powder (colour RAL 5015)	
Powder grit size	50 – 500 μ	
Density	1,22 g/cm ³ at 20 °C	DIN 53.479
Shore hardness	85 A	DIN 53.505
Melt Flow Index (MFI)	acc. to customer specification	
Melting range	135 – 145 °C	KOFLER
Softening range	120 – 130 °C	KOFLER
Hydrolysis resistance	Good	
Solubility	Good soluble in DMF and THF. The resistance of the films produced with DANTHANE® 125KB-Powder to all organic solvents is good, respectively the films will show a swelling behaviour by the influence of these solvents.	

MECHANICAL VALUES

	Values	Method
Tear strength	25 MPa	DIN 53.504
Elongation at break	610 %	DIN 53.504
Modulus 100 % elongation	5,5 MPa	DIN 53.504
Modulus 200 % elongation	6,0 MPa	DIN 53.504
Modulus 300 % elongation	8,5 MPa	DIN 53.504
Compression set (70 hrs./23 °C)	30 %	DIN 53.517
Compression set (24 hrs./70 °C)	80 %	DIN 53.517
Abrasion loss	30 mm ³	DIN 53.516
Glass transition temperature (Tg) (DSC, 10 °C/min.)	-29 °C	DIN 51.007



APPLICATION

DANTHANE® 125KB-Powder is applied at the hot melt coating of industrial textiles. The coated textiles are used for transport and drive sections. This TPU powder, coloured in blue, can be used at the coating as intermediate layer and final coating. Very often DANTHANE® 125KB-Powder is used as intermediate layer and then as top coat the transparent type DANTHANE® 125K-Powder is used. For the coating of textiles we also deliver the corresponding impregnations and primers with the DANCOLL® products.

PROCESSING

DANTHANE® 125KB-Powder is suitable for a lot of powder coating applications. We recommend DANTHANE® 125KB-Powder for:

- sinter coating
- dot point coating
- double dot point coating
- powder coating
- powder impregnation

Before the textiles will be coated, an impregnation and primer must put on. Concerning this we refer to the DANCOLL® product range.

COMPATIBILITY

DANTHANE® 125KB-Powder can be modified with flow regulation agents and additive wax, respectively stearates. This TPU powder has also a good compatibility to PVC coating raw materials and will be applied for this reason as PVC modifier.

STORAGE

If correctly stored in a dry and cool place in its original packing, this product can be stored for at least 6 months. The product needs to be protected from humidity.

PRODUCT SAFETY

DANTHANE® 125KB-Powder is under normal hygienic processing conditions a harmless material. If larger quantities are being processed in the melt, vapour extraction must be ensured.

* For further information we refer to our Safety Data Sheet

PHYSIOLOGICAL CHARACTERISTICS

With regard to physiological aspects, the product DANTHANE® 125KB-POWDER is a harmless material to a large extent. For the release for applications in the food and medical sector it must be fulfilled corresponding requirements. If you intend to use the product in these two sectors, we kindly ask you to contact us.

RECYCLING

Clean and uncontaminated waste of DANTHANE® 125KB-Powder, which was separated from the substrate, may be grinded and reused as grinding material or may be added to new TPU material.



PACKAGING

25 kg special antistatic bags, packed on pallets of 500 kg. The pallets are wrapped with PE shrink films. The delivery of 500 kg euro-pallets with PE shrink wrapping film meets the requirements of the F.R.G. transport packing regulations. Additionally, PE-lined cardboard bigbags of 700 kg net weight are available.



STÖRRENSTR.30 72135 DETTENHAUSEN GERMANY

: +49 (0)7157 5225-0

: +49 (0)7157 5225-22

: info@danquinsa.com

WWW.DANQUINSA.COM

Post office box 147 72133 DETTENHAUSEN GERMANY

STAND 08/2022